

Customer reference : SS0166

CAIGUNA 2131039

ORLAB reference : 21280.6

ORLAB method : ORLAB 2.53.3

Date of issue : 7 February 2022

Date tested : 12 January 2022

Ms Ashlie Callinan Sunshades Unit A/110 McEvoy St Alexandria NSW 2015 Optics & Radiometry Laboratory School of Optometry and Vision Science Room LG22 Old Main Building (K15) Gate 14, Barker Street

UNSW SYDNEY NSW 2052 Phone: +61 2 9385 4622 Fax: +61 2 9313 8602 E-mail: orlab@unsw.edu.au

<u>EVALUATION TESTS TO</u> Consumer Goods (Sunglasses and Fashion Spectacles) Safety Standard 2017

Submitted for test by : Sunshades

Supplier : Sunshades

Manufacturer : Not supplied

Identifier : 21280-6

DESCRIPTION OF SAMPLE

	Material	Colour(Colour(s)				
Frame front	Plastic	Matte bl	Matte black				
Sides	Plastic	Brown to	Brown tortoiseshell				
Side ends	None	N/A	N/A				
	Material	Colour(s)	Tint	Туре	Coating	
Filters	Plastic	Brown		Uniform	Polarising	Unknown	
Markings	Front	None	None				
	Filters	None					
	Right side	Inside	CAIGU	NA 2131039		Outside	None
	Left side	Inside	CANCE	R COUNCIL	- POLARISED	Outside	None
Packaging	None						
Stick on label	None						
Swing-tag	Refer to photo						

This report may not be published except in full unless permission for the publication of an approved extract has been obtained in writing.





Accredited for compliance with ISO/IEC 17025 - Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports

AA

Page 1 of 6

Checked by

Report No. 21280.6







SECTION 4 CONSTRUCTION AND MATERIALS

4.1 Construction Pass

SECTION 5 TRANSMITTANCE

5.2 TRANSMITTANCE AND FILTER CATEGORIES

Light tint sunglasses	Category 0	over 80%	to	100%
Light tint sunglasses	Category 1	over 43%	to	80%
General purpose sunglasses	Category 2	over 18%	to	43%
General purpose sunglasses	Category 3	over 8%	to	18%
Very dark special purpose sunglasses	Category 4	over 3%	to	8%

Minimum spectral transmittance for wavelengths 475nm − 650nm $\geq 0.20\tau_V$

Minimum relative visual attenuation for signal light detection (Q) Red ≥ 0.80 Blue ≥ 0.70 Yellow, Green ≥ 0.60

UV spectral range 280-315nm 315-400nm Maximum Category 0 - 1 0.05 $\tau_{\rm V}$ $\tau_{\rm V}$

Category 2 -3 $0.05 \tau_{\nu}$ $0.5 \tau_{\nu}$

Category 4 0.05 $\tau_{\rm v}$ 1.0% absolute or 0.25 $\tau_{\rm v}$

	Right Eye	Left Eye	Compliance
280-315nm (%)	<0.1	<0.1	Pass
315-400nm (%)	<0.1	<0.1	Pass
Min Spect Trans	0.38	0.38	Pass
Tv (%)	15.0	14.9	
Category	3	3	Category 3
Q _{Red}	1.57	1.58	Pass
Q _{Yellow}	1.24	1.25	Pass
Q _{Green}	0.86	0.86	Pass
Q _{Blue}	0.67	0.67	Warning required

This report may not be published except in full unless permission for the publication of an approved extract has been obtained in writing.





Accredited for compliance with ISO/IEC 17025 - Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports

Report No. 21280.6 Page 2 of 6 Checked by

See below



5.3 GENERAL TRANSMITTANCE REQUIREMENTS

5.3.1 Uniformity of luminous transmittance

See below

Transmittance matching (relative to the lighter filter)

Maximum

≤ 15%

Right Eye	Left Eye	Matching	Compliance
14.9%	15.0%	0.6%	Pass

5.3.2 Requirements for road use and driving

5.3.2.1 General

5.3.2.2 Spectral transmittance Refer to clause 5.2
5.3.2.3 Detection of signal lights Warning required
5.3.2.4 Driving in twilight or at night (Category 1-3) Warning required

5.3.3 Wide angle scattering

See below

Haze Maximum ≤ 3.0%

Right Eye	Left Eye	Compliance
1.5%	1.6%	Pass

5.3.4 Additional transmittance requirements for specific filter types

5.3.4.1 Photochromic filters

N/A

5.3.4.2 Polarizing lenses

See table below

Plane of polarization Maximum Individual lens ≤ 5° Misalignment of lenses ≤ 6° Ratio of luminous transmittance Maximum Lens categories 2,3,4 ≥ 8:1

Lens category 1 $\geq 4:1$

	Right Lens	Compliance	Left Lens	Compliance	Misalignment	Overall Compliance
Plane of Polarization	-0.5°	Pass	-0.5°	Pass	0.0°	Pass
Ratio of Luminous Transmittance	35:1	Pass	35:1	Pass	N/A	Pass

5.3.4.3 Gradient filters N/A

5.3.5	Claimed transmittance properties	No claims made
5.3.5.3	Antireflective coated sunglasses	No claims made
5.3.5.4	Enhanced infrared absorption	No claims made

This report may not be published except in full unless permission for the publication of an approved extract has been obtained in writing.





Accredited for compliance with ISO/IEC 17025 - Testing

Report No. 21280.6 Page 3 of 6 Checked by

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards



SECTION 6 REFRACTIVE POWER

6.1 SPHERICAL AND ASTIGMATIC POWER

See below

Spherical PowerLimit \pm 0.12 DSpherical Power DifferenceMaximum0.18 DAstigmatic PowerMaximum \pm 0.09 D

Spherical Power (dioptre)					
Right Eye Compliance Left Eye Compliance Difference Compliance					
-0.054	Pass	-0.046	Pass	0.008	Pass

Astigmatic Power (dioptre)			
Right Eye	Compliance	Left Eye	Compliance
0.013	Pass	0.002	Pass

6.2 LOCAL VARIATIONS IN REFRACTIVE POWER

Not required

6.3 PRISM IMBALANCE (RELATIVE PRISM ERROR)

See below

Prism imbalance Maximum Vertical $\leq 0.25 \,\Delta$ Horizontal (in) $\leq 0.25 \,\Delta$ Horizontal (out) $\leq 1.00 \,\Delta$

Base In / Out	Horizontal	Compliance	Vertical	Compliance
Out	0.16	Pass	0.01	Pass

SECTION 7 ROBUSTNESS

7.1 GENERAL See below

7.2 FRAME DEFORMATION AND RETENTION OF FILTERS Pass

7.3 ROBUSTNESS AND FILTER RETENTION, STRENGTH LEVEL 1 Pass

SECTION 9 RESISTANCE TO IGNITION

Material known and tested previously

SECTION 11 PROTECTIVE REQUIREMENTS

11.1 COVERAGE AREA

Pass

11.2 TEMPORAL PROTECTIVE REQUIREMENTS

N/A

This report may not be published except in full unless permission for the publication of an approved extract has been obtained in writing.





Accredited for compliance with ISO/IEC 17025 - Testing

Report No. 21280.6 Page 4 of 6 Checked by



AA

SECTION 12 INFORMATION AND LABELLING

12.1 INFORMATION TO BE SUPPLIED WITH EACH PAIR OF SUNGLASSES

The manufacturer shall provide the following information in the form of markings on the frame or on labels, packaging, etc., that accompanies the sunglasses at the point of sale.

(a)	Identification of model	Present
(b)	Name and address of the manufacturer/supplier	Required

(d) Type of filter, if photochromic and/or polarizing
 (e) Number of the filter category
 (f) Description of the filter category in the form of category number, description and usage as given in Table 5 (symbol min height 5mm)

(g) Restrictions of use, which shall include at least the following-Not for direct observation of the sun; Not for protection against artificial light sources, eg. solaria

Not for use as eye protection against mechanical impact hazards Any other restrictions deemed appropriate to be communicated by the manufacturer

Instructions for care and cleaning (if relevant)

Not provided

12.2 ADDITIONAL INFORMATION

The following information shall be available from the manufacturer on request.

- (b) The position of the reference point when different from the one defined in this Standard.
- (d) The nominal value of luminous transmittance
- (e) Transmission requirements applicable to this product
- (f) Polarization efficiency in cases of polarising filters
- (g) The base material of filters and frame

12.3 METHODS OF MARKING AND LABELLING

12.3.1	Form of labelling	Not seen
12.3.3	Legibility	Not seen

This report may not be published except in full unless permission for the publication of an approved extract has been obtained in writing.





These sunglasses DO meet the requirements of the Consumer Goods (Sunglasses and Fashion Spectacles) Safety Standard 2017, provided the additional information as required in Section 12 accompanies the glasses.

The Standard requires these sunglasses be accompanied by the appropriate labelling as specified below.

- a) Identification of model
- b) Name and address of the manufacturer

Filter category, type (polarising) and description

See below

Filter category	Description	Usage	Additional required information	Symbol
3	General purpose sunglasses	High protection against sunglare Good UV protection	Not suitable for driving in twilight or at night; or not suitable for driving at night or under dull light conditions	

NOTE: Use of the pictograms is optional. If used the min height of the symbols shall be 5mm.

(g) Restrictions of use

(h) NOT SUITABLE FOR DRIVING AND ROAD USE





(i) Instructions for care and cleaning (if relevant)

Ashley Ang

Authorised Signatory

Notes: The uncertainties stated in this report have been calculated in accordance with principles in the ISO Guide to the Expression of Uncertainty in measurement, and give intervals estimated to have a level of confidence of 95%. A coverage factor (k) of 2.0 was used.

The following least uncertainties for the measurements reported have been taken into account when assessing compliance:

This report may not be published except in full unless permission for the publication of an approved extract has been obtained in writing.





Accredited for compliance with ISO/IEC 17025 - Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

Report No. 21280.6 Page 6 of 6 Checked by

